



## DATASHEET

## DPG

## PO &amp; DERIVATIVES

U1521

Revised December 2019

DPG is a mixture of dipropylene glycol (DPG) isomers. It is a clear, colourless and odourless, hygroscopic liquid, completely soluble in water.

DPG is miscible in all proportions with low molecular weight aliphatic alcohols and ketones. It is slightly to moderately soluble in aromatics hydrocarbon solvents and only slightly miscible with aliphatics hydrocarbon solvents.

Other chemical names for DPG are: Oxydipropanol

$(\text{OH})\text{C}_3\text{H}_6\text{-O-C}_3\text{H}_6(\text{OH})$

## TYPICAL PROPERTIES

| PROPERTY                       | TEST METHOD | UNIT                 | VALUE    |
|--------------------------------|-------------|----------------------|----------|
| Purity                         | ASTM E-202  | % (m/m)              | 99.5 min |
| Colour                         | ASTM E-202  | Pt-Co                | 10 max   |
| Water                          | ASTM E-202  | % (m/m)              | 0.1 max  |
| Acidity as Acetic Acid         | ASTM E-202  | % (m/m)              | 0.01 max |
| Iron                           | ASTM E-202  | ppm                  | 1.0 max  |
| Molecular weight               |             | g/mol                | 134.2    |
| Density                        |             | Kg/m <sup>3</sup>    | 1027     |
| Coefficient of cubic expansion |             | 10 <sup>-4</sup> /°C | 7.4      |
| Refractive index               |             |                      | 1.4415   |
| Pour point                     |             | °C                   | -47      |
| Boiling point                  |             | °C                   | 229-232  |
| Flash point                    |             | °C                   | 149      |
| Vapour pressure at 20 °C       |             | Pa                   | <1       |
| Vapour pressure at 50 °C       |             | Pa                   | 16       |
| Vapour density (air=1)         |             |                      | 4.6      |
| Dynamic viscosity              |             | mPa.s                | 84       |
| Surface tension at 25°C        |             | mN/m                 | 33.55    |
| Specific heat                  |             | kJ/kg K              | 2.107    |
| Latent heat of evaporation     |             | kJ/kg                | 593.2    |
| Thermal conductivity           |             | W/m K                | 0.149    |
| Heat of combustion at 25°C     |             | MJ/kg                | 25.6     |
| Electrical conductivity        |             | µS/m                 | 0.19     |
| Dielectric constant            |             |                      | 21       |

All typical physical properties are at 20°C unless stated otherwise. The above typical physical properties are published here as a guide to potential users of the product. A sales specification is published separately.

# DPG

## PO & DERIVATIVES

### Application

Dipropylene Glycol finds its largest application in the plasticizer market, mainly as an dibenzoate. The second large market for DPG is in unsaturated polyester resins. Other applications are in urethane polyols, alkyd resins, functional fluids like de-icer formulations, inks and paints and as a solvent in fragrances and cosmetics.

### Test Methods

Copies of copyrighted test methods can be obtained from the issuing organisations:

American Society for Testing and Materials (ASTM): [www.astm.org](http://www.astm.org)

For routine quality control analyses, local test methods may be applied that are different from those mentioned in this datasheet. Such methods have been validated and can be obtained through your local Shell Chemicals company.

### Storage and Handling

DPG is slightly hygroscopic and must be stored under conditions so that contamination with water and absorption of moisture are prevented. Contact with copper, copper alloys or zinc must be avoided.

The storage temperature of DPG is not critical, in that there will be no hazardous conditions created by the storage of the product at any ambient temperature likely to be encountered. DPG is a stable product and its processing performance is not expected to deteriorate significantly with time providing it is stored as described above.

The shelf life of DPG is 24 months. As a good industrial practice, however, it is recommended that DPG be used within 12 months from opening of the sealed package.

For further advice on Storage and Handling please refer to the Safety Data Sheet on [www.shell.com/chemicals](http://www.shell.com/chemicals)

### Hazard Identification

Low order of acute toxicity by the oral or precutaneous routes. Slightly irritating to the eyes and skin. This product is not in the 'flammable' range, but will burn. Before handling the product, please refer to the Safety Data Sheet.

| PROPERTY                     | TEST METHOD | UNIT    | VALUE |
|------------------------------|-------------|---------|-------|
| Flash point (PMCC)           | ASTM D93    | °C      | 149   |
| Lower explosive limit in air |             | % (v/v) | 1     |
| Upper explosive limit in air |             | % (v/v) | 3     |
| Auto ignition temperature    |             | °C      | 260   |

### DISCLAIMER

The expression 'Shell Chemicals' refers to the companies of the Royal Dutch / Shell Group which are engaged in chemical businesses. Each of the companies which make up the Royal Dutch / Shell Group of companies is an independent entity and has its own separate identity.

The information contained in this publication is to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.